

ZIPWAKE Trimkontrollsystem



ArtNr	Modell	Mått	Pris inkl moms
94450	KIT 300S	300mm	16 800
94452	KIT 450S	450mm	18 000
94454	KIT 600S	600mm	19 200
94456	KIT 750S	750mm	20 500



ARTNR	TYP	LÄNGD.	Pris inkl moms
94460	INTERCEPTOR 300S	300mm	4 300
94462	INTERCEPTOR 450S	450mm	4 900
94464	INTERCEPTOR 600S	600mm	5 500
94466	INTERCEPTOR 750S	750mm	6 100

Pris inkl moms

94470	Zipwake kontrollpanel	6 900
-------	-----------------------	-------

Fullfunktions kontrollpanel för Zipwake systemet. Panelen behövs där dubbla kontrollpaneler behövs t.e.x flybridge.

SPECIFICATIONS

Model CP-S

Display 2.4" Transflective color TFT, 320 x 240 pixels, double-sided, anti-reflection coated window

Internal sensors 5 Hz GPS, 3D Gyro, 3D Accelerometer, Ambient light

Supply Voltage 12 - 32 V DC

Power Consumption 10 W max

Operating Temperature -20° to +85°C

Storage Temperature -40° to +90°C

Waterproof Rating IP67 / IP64 (front / back)

Compass Safe distance 0.5 m

Compliance CE, FCC


Mounting Flush or surface

INTERFACES I-BUS IN (CAN bus) I-BUS OUT (CAN bus) NMEA 2000 External GPS

(NMEA 0183 / RS232 auto baud-rate sensing) Key Sense USB Device Port (Type A)

USB Host Port (Type B)

Pris inkl moms



94474	FÖRLÄNGNINGSKABEL 1,5M	460
94475	FÖRLÄNGNINGSKABEL 3M	580
94476	FÖRLÄNGNINGSKABEL 5M	650
94477	FÖRLÄNGNINGSKABEL 10M	830

Frakt tillkommer